SpeedStream USB DSL Modem





FAST, POWERFUL

SpeedStream® USB DSL modems provide full-rate ADSL for up to 8 Mbps downstream, 1 Mbps upstream for the true broadband experience. View streaming video, play interactive games and trade stocks online at blazing speeds.



SIMPLE INSTALLATION, EASY-TO-USE

Plug-and-play simplicity makes installation a snap, while the comprehensive graphical interface of the SpeedStream® DSL Software makes set-up and operation worry-free.



AUTOMATIC ASSISTANCE

SpeedStream® DSL Software performs network analysis, senses DSL network characteristics and automatically configures the modem. On-board diagnostics and reporting streamline installation and set-up and provide a clear reference for any troubleshooting.

USB DSL Modems



SpeedStream® USB DSL Modems are the simplest
DSL solution for end-users. With plug-and-play
for worry-free installation, these high-performance,
stand-alone DSL modems can be installed on a
desktop or notebook without ever opening the compute

SpeedStream® DSL Software analyzes the DSL network and configures the USB modem thus ensuring correct, worry-free consumer installation. The on-board diagnostics detect potential issues and resolve problems automatically — virtually eliminating the need to call sech support.

SpeedStream® USB DSL Modems make high-bandwidth applications such as interactive gaming, streaming video and real-time audio a true pleasure.

Powerful, versatile, and easy-to-use — get a SpeedStream® USB DSL Modem from Efficient Networks® and experience the broadband world today!



SpeedStream USB DSL Modems

Features and Benefits


- Encapsulation with Ethernet over ATM, IP over ATM and PPP over ATM.
- Discrete multi-tone ADSL ensures interoperability with service providers.
- Speeds of up to 8Mbps downstream and 1Mbps upstream
- Rapid broad-scale deployment via configuration profiling
- Easy field upgrade with feature enhancements.
- Seamless integration for Windows® Me. 2000, and 98.

SpeedStream® DSL Software

- Senses DSL network characteristics and configures the modem to match.
- Diagnostics analyze hardware, software, and network status
- Diagnostic reports are saved for use as reference during support calls.
- Intuitive graphical interface assures successful installation.

SpeedStream® USB DSL Modem





SpeedStream® 4000 Series

To learn more about the SpeedStream® USB DSL modem visit: www.efficient.com

Technical Specifications

Form Factor:

External Universal Serial Bus Specification 1.1

Dimensions

5.5W x 7D x 1.5 H in. (14W x 17.8D x 3.8H cm)

Weiaht:

1.25 lbs. (0.57 Kg)

Power Requirements:

External 110-240 VAC, 50-60 Hz power supply 0.1A max @ 110 VAC, 0.08A max @ 240 VAC

AAL and ATM Support:

Integrated ATM AAL5 support 255 VPI plus 65535 VCI address range Precise (up to 1Kbps) peak cell rate traffic shaping

Physical Layer

Alcatel Microelectronics Discrete Multi-Tone Asymmetric Digital Subscriber Line, compliant with ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt), ITU G.992.2 (G.lite)

ADSL interface:

Standard telephone wiring

USB interface:

Compliant with Universal Serial Bus Specification 1.1; Standard USB interface cable included

Environment

Operating temperature: 0°C to 40°C

Non-operating storage temperature: -10°C to 85°C Operating humidity: 10% to 90% non-condensing

Non-operating storage humidity: 5% to 95% non-condensing

Compliance and Certification

UL1950, CSA, CE, EN60950, FCC Part 15 Class B, CISPR Class B, FCC Part 68

Visual Indicators

LED indicates network status

Warranty

1 year parts and labor for hardware Software updates via Web site



Corporate Headquarters: Efficient Networks, Inc. 4849 Alpha Road Dallas, TX 75244 +1(972) 852-1000 Fax +1(972) 852-1001 E-mail info@efficient.com

Efficient Networks Europe B.V. Parc Centre Boeing Avenue 8 1119 PB Schiphol-Rijk The Netherlands. +31 (0)20 655 60 65 Fax +31 (0)20 655 60 65 Fmall europe@efficient com

Efficient Networks Asia Pte Ltd. Level # 19-05 Suntec Tower Two No. 9 Temasek Boulevard Singapore 038989 +65 3385855 Fax +65 3385860 Fmail asianac@efficient com